



Multi - Mount in popular sizes 5 to 34W.

Specifications:

- Multi-mount - front / back / top / bottom M4 mounts , 14 points
- Rated at 30,000 hours continuous running, S1 rated
- Power lead 1 meter , 3 core
- Mounting nuts, washers & screws provided
- Protection IP42
- Operating temperature range -30 to +50°C
- Insulation class B
- CE, VDE,UL, CCC approved

Henry Part Number	Output Watts W	Power input W (Rated)	Current amps	Speed rpm	Air flow m ³ /hr	Fan blade mm	Rated supply VSC/Hz	Weight kg
SPQ-5-13-18/26	5	29	0.20	1300	455	Ø200	220-240/50	0.80
SPQ-10-20-18/26	10	36	0.25	1300	650	Ø230	220-240/50	1.10
SPQ-16-25-18/26	16	60	0.45	1300	760	Ø230	220-240/50	1.40
SPQ-25-40-18/26	25	90	0.70	1300	1030	Ø300	220-240/50	1.80
SPQ-34-45-18/26	34	110	0.85	1300	1210	Ø300	220-240/50	2.00

Dimensions:

Henry Part Number	Output Watts W	A mm	B mm	C mm	D mm	E mm
SPQ-5-13-18/26	5	13	15	46	82	45
SPQ-10-20-18/26	10	19	15	46	88	51
SPQ-16-25-18/26	16	25	14	45	94	56
SPQ-25-40-18/26	25	40	18	49	113	75
SPQ-34-45-18/26	34	45	22	53	122	84

