



Tolleranze di lavorazione: ISO 2768-C

Item Number	Description	Quantity
1	HEAD Ø168	2
2	TUBE Ø168,3	1
3	TUBE Ø22	1
4	BASE SUPPORT Ø168 H60X180X40 H.Ø12	2
5	COMPRESSOR SUPPORT 550X350X60 F.Ø11	1
6	1/2" NPT-F	1
7	ROTALOCK 1 1/4 - 12 UNF	2
8	SIGHT GLASS SLEEVE 26X1.5	2
9	SIGHT GLASS 26X1,5	2
10	SIGHT GLASS GASKET 26X1.5	2
11	LABEL	1

Rev.	Data-Date	Dis.-Draftsman	Visto-Checked by	Descrizione Revisione - Revision Description
Denominazione - Denomination				Codice Disegno - Drawing Code
<b>RLH H.LIQ.REC.18LT. Ø168X900 PS32BAR</b>				<b>BORRO1680900B</b>
PS - Design	PW - Work	PT - Test	Temperatura - Temperature	Refrigerant
32 BAR	32 BAR	48 BAR	-10°C +100°C	HFC - HCFC
Scala - Scale	Data-Date	Disegnatore - Draftsman	Visto-Checked by	Categoria PED
1:6	11.04.2014	S.ZANON	S.SPINELLO	II
Materiale - Material	Spessore - Thickness	Colore Vernice-Painted Color	Prodotto e Realizzato Secondo Direttiva 97/23/CE	Peso - Weight [kg]
-	-	RAL 9005 - BLACK	Produced and Made According to Directive 97/23/CE	25.17
				Cod.STD

