



| | | |
|----|-------------------------------------|---|
| 14 | LABEL | 1 |
| 13 | ROVALOCK VALVE 1"1/4 ODS 1/2" (Ø12) | 1 |
| 12 | ROVALOCK VALVE 1"1/4 ODS 5/8" (Ø16) | 1 |
| 11 | GASKET "PTFE "FOR ROVALOCK 1"1/4 | 2 |
| 10 | SIGHT GLASS GASKET FOR M26X1.5 | 1 |
| 9 | SIGHT GLASS M26X1,5 | 1 |
| 8 | SCREW M10X30 | 1 |
| 7 | SIGHT GLASS SLEEVE FOR M26X1.5 | 1 |
| 6 | ROVALOCK 1"1/4 | 2 |
| 5 | 3/8" NPT-F | 1 |
| 4 | BASE SUPPORT Ø140 | 1 |
| 3 | TUBE ODØ22 | 1 |
| 2 | DEEP HEAD Ø220 TRIMMED | 1 |
| 1 | DEEP HEAD Ø220 RIMMED | 1 |



OCS COLD S.R.L.
Via L.Da Vinci, 8 35020 Brugine (PD) ITALY
Tel. +39 049 9730184 - Fax +39 049 5806885
www.ocscold.it - info@ocscold.it

RAL 9005 BLACK POWDER COAT



CODE



BORRL2200400B

| | | | |
|-----------------|--------|------------------------------------|-----------|
| VOLUME | 14L | CUSTOMER CODE | |
| MAX PRESSURE | 32 BAR | SERIAL N° | |
| TEST PRESSURE | 48 BAR | REFRIGERANT | HFC, HCFC |
| MIN TEMPERATURE | -40°C | FLUID GROUP(Art.13 Dir.2014/68/EU) | 2 |
| MAX TEMPERATURE | +100°C | PED CATEGORY | II |
| WEIGHT | 8.94KG | NOTIFIED BODY | 0948 |

| | | | |
|---|-----------|------------|-----------|
| SHEET 2 of 2 | SCALE 1:5 | S.SPINELLO | G.BOKARIS |
| GENERAL TOLLERANCE ACCORDING TO ISO2768-C | | CHECKED BY | DRAFTSMAN |

| | | |
|------------|--|---|
| 13/09/2016 | RLV 14L Ø220X400 +RV ODSØ5/8"-1/2" PS32BAR -40°C | 1 |
| 19/04/2016 | AGGIORNATA TEMPERATURA | 1 |